


Breadth of Scientific Activities and Network Station Specifications in the IGS



Moore, A.W.; Neillan, R.E.

Jet Propulsion Laboratory, California Institute of Technology

Springer, T.A.

Astronomical Institute, University of Bern

Reigber, Ch.

GeoForschungZentrum Postdam



A Very Brief History of the IGS

- Approved activity of the International Association of Geodesy (IAG) with official start of service 1 Jan 1994. FAGS service since 1996.
- Mission: "To provide a service to support geodetic and geophysical research activities, through GPS data and data products."
- Network infrastructure and products were in large part originally commissioned for geodynamical investigations

Quality of the IGS Products

Products	Predicted*	Rapid*	Final	
Delay	Real Time	17 hours	11 days	Units
Orbit	50.0	10.0	5.0	cm
Clock	150.0	0.5	0.3	ns
Pole		0.2	0.1	mas
LOD		30.0	20.0	μ s/d
Stations			5.0	mm
Troposphere			1.0	mm PWV
Geocenter			30.0	mm
Terrestrial Scale			2.0	ppb

* 24-48 Hour prediction; AC's provide also 0-24 Hour predictions
 * AC products available at 8:00 Hours UTC



IGS Working Groups and Pilot Projects

- A Working Group works on a particular topic related to the IGS components according to goals and schedule specified in the working group's charter.
- A Pilot Project aims at the development of particular IGS product(s) or service(s) relying on the IGS infrastructure.
- Both established by the Governing Board
- Generally "new directions" come from a working group or pilot project.

4




Current Working Groups and Pilot Projects

- Reference Frame Coordination; R. Ferland
- IGS/BIPM Time Transfer Project; chairs J. Ray and G. Petit
- Ionosphere WG; chair J. Feltens
- Troposphere WG; chair Gerd Gendt
- International GLONASS experiment; chair P. Willis
- Low-Earth Orbiter WG; chair M. Watkins
- Tide Gauges, CGPS, and the IGS (seed activity); chair M. Bevis

5

GPS TRACKING NETWORK

International GPS Service



April 1999




Carrying Out Project(s)

- May require specialized instrumentation
- May require specialized operating methodology
- Will require organization and guidance to participants

Network stations end up described as points in N-dimensional instrumentation & location space (!)



6



Ionosphere Working Group

- Formed 28 May, 1998
- Short-term goal of global ionosphere total electron content (TEC) maps with delay of about one week (realized)
- Only very preliminary comparison/combination at this time
- Long-term goal of near real-time or real-time TEC availability
- Implies global coverage of low latency stations


7





Troposphere Working Group

- Zenith neutral delay (ZND) estimates are a usual IGS product since 1997
- Approximately 80 sites analyzed by >2 ACs



10



Troposphere Working Group

- Precise meteorological sensors required for calculation of precipitable water vapor (PWV) from ZND. It is now recommended to install a precise barometer at all IGS sites.
- Met sensors number only 30 and so far, can be problematic (with respect to data dropouts, etc)
- Latency requirement not stringent at present due to low density of sites with met sensors

11



Tide Gauges, CGPS, and the IGS

- IGS has an advisory role in the deployment of continuous GPS stations at tide gauges
- Technical committee producing station standards document
- UH Pacific GPS Facility & Sea Level Center installing 3rd & 4th stations now
- Around 20 globally distributed stations forseen for the purpose of calibrating satellite altimeters

12



Tide Gauges, CGPS, and the IGS

- Being co-located with tide gauges, these stations are often (geodetically speaking) poor in terms of stability
- Communications also poor; latency is not a concern, but delays of weeks to months for data delivery means "classic" IGS processing will not be performed

13





IGEX-98 (International GLONASS Experiment)

- Joint working group of CSTG, IGS, & ION, with IERS sponsorship. Oct 18-Apr 17.
- Motivations
 - No SA or AS on GLONASS
 - Combined system 41 satellites
- Objectives
 - Precise GLONASS orbits (1m or better)
 - evaluation of orbits by SLR
 - evaluate improvement of positioning capabilities over GPS alone
 - Compare PZ-90 with WGS84 and ITRF
- IGEX workshop before ION, Nashville, Sept.

14




Broadcast GLONASS orbits compared to IGEX orbits



15

IGEX






IGS/BIPM Time Transfer Project

- Objectives
 - Exploit GPS pseudorange & carrier phase data to determine satellite & receiver clocks
 - Calibration measurements to provide access to UTC via external standards at timing labs
 - Global time & frequency transfer with potential accuracy $<200\text{ps}$
- Other long-distance time transfer techniques: comparisons at ns-level
- IGS stations located at timing laboratories (currently 11) enable improved maintenance of international atomic time scale

16




IGS/BIPM Time Transfer Project: Instrumentation

- Timing applications highly sensitive to delays
 - receiver
 - antenna
 - cable (!)
 - temperature effects on all of these
- Especially important for site changes to be promptly communicated to analysts

17


Fiducial clock





Working Group on Low Earth Orbiters

- Chartered to explore the role of LEOs in IGS
- Many LEO missions coming soon



18

~~(insert Ruth's LEO table)~~

DISREGARD
AWM

19

LEO Mission Matrix of Basic Characteristics*

Mission	Agency Processing Center	Sample Rate (SV)	Download Frequency* Occultation POD data/ Download	Downlink Station Location	Daily Data Volume for Flight	Nominal Orbital Elements	Website or Further Information Notes
Oersted 2/99 14 mo.	Danish Meteorological Institute (DMI)	10 Hz	? 2.6 MB	Copenhagen, Aalborg, IKT (Denmark)	5.2 MB	h= 500- 850 km, elliptical polar orbit, i=~85°	http://gate.dmi.dk/fsweb/projects/oersted
Sunsat 2/99 ~5 years	Univ. of Stellenbosch Sth. Africa	50 Hz	2/day	Sth. Africa, Stellenbosch Univ.	20 MB	h=650- 820 km, elliptical polar orbit	http://sunsat.ee.sun.ac.za/index.html SLR retroreflectors
CHAMP 12/99 5 years	GFZ/DLR	0.1-50 Hz	2/day 10 MB	Neustrelitz, Germany	20 - 90 MB	h=470 km, i=87°	http://www.gfz-potsdam.de/pb1/CHAMP/champ.htm NADIR ANTENNA SLR retroreflectors
SAC-C 10/99 4 years	CONAE, Argentina	0.1-50 Hz	2/day 10 MB	Cordoba, Argentina	20 MB	h=707 km, quasi-polar circular, sun synch	http://www.conae.gov.ar/caratula.html link to SAC-C 1 ANTENNA
ICESat/GLAS July 2001 3 years	NASA/EOS					h=600 km, circular 'frozen', i= 94°	http://www.csr.utexas.edu/glas/ http://icesat.gsfc.nasa.gov/ SLR retroreflectors
GRACE (2 sv's) June 2002 5 years	NASA/GFZ	0.1-50 Hz	2/day ~40 MB (10 MB/sv/pass)	Neustrelitz, Waldheim, Germany	~100 MB	h=500 km, i= 87°	http://www.csr.utexas.edu/grace/ SLR retroreflectors
COSMIC (ROCSAT-3) (~8svs) 2002 2 - 5 years	National Space Program Office, ROC UCAR	100 Hz	every 100 min 5 MB/sv/pass	Taiwan, Fairbanks, Kiruna	~400-600MB	h=400 - 700 km sv stacking, i=75°	http://www.nspo.gov.tw/e30/welcome.html NSPO, COSMIC = ROCSAT-3 & http://www.gst.ucar.edu/ Includes COSMIC and GPSMet
GOCE 2003 - 2005 6-8 mo.	ESA/ESTEC					h=260 km, i=96.5 circular sun-synch	http://www.estec.esa.nl/vrwww/EXPLORER.html

Not all fly the JPL developed receivers

JPL GPS flight receiver information: <http://rogueweb.jpl.nasa.gov>

* DOES NOT INCLUDE ALTIMETRY MISSIONS; TOPEX/POSEIDON, GPSMET, GFO, JASON, METOP, EUMETSAT, FEDSAT, ..

~1200 OCCULTATIONS/DAY


4000 OCC. PER DAY



JPL/GFZ/IGS LEO Workshop March 1999, Potsdam

- Recommendation 1: committee to codify standards for ground stations
 - high-rate (1s) data
 - subhourly downloads
 - low latency => reliable, high bandwidth comm
 - track <20 degrees

20




LEO Network Communications


- Global realization of low-latency and higher data-rate operation is necessary
- May be beneficial to utilize a common commercial solution for particularly remote areas
- Demonstration project for high-rate data communications with VSAT organized by UNAVCO

21

Proposed CHAMP Ground GPS Network



Hourly RINEX






LEO Workshop other recommendations

- Analysis centers to voluntarily demonstrate ultrarapid analysis product (orbit, clock, EOP, and predicts) with <3hr latency mid-99
- Exchange of larger volumes of LEO ground support data implies a binary format. Subcommittee formed.
- 3-6 month Pilot Project to begin 8/99 with 1Hz data in new binary format will evaluate impact of flight data in IGS products. Call for participation to be issued.

22



Wrap-up

- IGS moving quickly in multipurpose arenas
- Network coordination is challenging!
- IGS Central Bureau Information System
<http://igscb.jpl.nasa.gov>
- Good summaries of projects in Annual Report & Network Workshop Proceedings (coming soon) online
- Thanks to all WG chairs

23